

Outlets RJ45 unscreened



Category 6 / Class E



Type

RJ-45 UP socket unscreened class E 2P vertical

RJ-45 UP socket unscreened class E 2P horizontal

Configuration

Housing material: Plastic
Colour: Pure White similar to RAL 9010
Board: 1x2
Push-on connector type: RJ45(8/8)
Outlet direction: 45 degrees
Number of bushes: 2
Type of screen: no
Strain relief: via pre-installed cable clips
Cable inlet: vertical

Housing material: Plastic
Colour: Pure White similar to RAL 9010
Board: 1x2
Push-on connector type: RJ45(8/8)
Outlet direction: 45 degrees
Number of bushes: 2
Type of screen: no
Strain relief: via pre-installed cable clips
Cable inlet: horizontal

Connecting system

Connection type: LSA plus - insulation piercing connections
Suitable for cable diameter: 0,4 - 0,64mm (AWG 26 - 22)
Insulation diameter, min.: 0,7 - 1,6 mm (PE)

Connection type: LSA plus - insulation piercing connections
Suitable for cable diameter: 0,4 - 0,64mm (AWG 26 - 22)
Insulation diameter, min.: 0,7 - 1,6 mm (PE)

Assignment type

EIA/TIA 568 A + EIA/TIA 568 B

EIA/TIA 568 A + EIA/TIA 568 B

Dimension

Norms and standards

HELUKAT® system component unscreened up to 250 MHz of category 6 or Class E in accordance with ISO 11801, EN 50173, ANSI/TIA/EIA 568 B2-1.

Application

As workstation interface in applications of digital and analog image, data and voice transmission. Available as in-wall version (channel) and top-mount version (possible with an extra frame).

Part no.

802909

803033

Dimensions and specifications may be changed without prior notice.

Packing unit

10

10