

# Outlets RJ45



Category 5e / Class D



## Type

### RJ-45 UP socket cat. 5e 2P horizontal

### RJ-45 UP socket cat. 5e 2P vertical

## Configuration

Housing material:

Colour:

Board:

Push-on connector type:

Outlet direction:

Number of bushes:

Type of screen:

Strain relief:

Cable inlet:

Die-cast, shielded

Pure White similar to RAL 9010

1x2

RJ45(8/8)

45 degrees

2

Overall screen

via pre-installed cable clips

horizontal

Die-cast, shielded

Pure White similar to RAL 9010

1x2

RJ45(8/8)

45 degrees

2

Overall screen

via pre-installed cable clips

vertical

## Connecting system

Connection type:

Suitable for cable diameter:

Insulation diameter, min.:

LSA plus - insulation piercing connections

0,4 - 0,64mm (AWG 26 - 22)

0,7 - 1,1 mm (PE)

LSA plus - insulation piercing connections

0,4 - 0,64mm (AWG 26 - 22)

0,7 - 1,1 mm (PE)

## Assignment type

EIA/TIA 568 A + EIA/TIA 568 B

EIA/TIA 568 A + EIA/TIA 568 B

## Dimension

Dimensions of central plate:

Installation dimensions:

50 x 50mm

51 x 51 x 29mm

50 x 50mm

51 x 51 x 29mm

## Norms and standards

HELUKAT® CONNECTING SYSTEMS® system component up to 100 MHz in category 5(e) / Class D in accordance with ISO 11801, 2nd edition, EN 50173, 2nd edition, EIA/TIA 568 B, and EN 55022 (EMC)

## Application

As workstation interface in applications of digital and analog image, data and voice transmission. Available as in-wall version (channel) and top-mount version (wall).

## Part no.

**82008**

**82853**

Dimensions and specifications may be changed without prior notice.

## Packing unit

**10**

**10**