

HELU-S-RK-45-CU-UL Copper tubular cable lug - 45° angled



Tubular cable lug angled HELU-S-RK-45-CU-UL

Non-insulated tubular cable lugs in eye type design, 45° angled.

Material


Socket: Copper according to DIN EN 13600
Surface: tin plated

Technical data

Temperature range: up to +120°C

Note

Compression instruction and instruction for assembly see chapter "Technical information".



Dimensions

- a Diameter of the boring
- d Inner diameter of the cable insertion
- b Flange width

eye type

Part no. 45°	Type	Cross-section mm ²	a mm	d mm	b mm	Weight kg / 1000 items	Unit	Net EUR/ 100 items at a purchase of		
								up to 100	101 - 500	501 - 1000
907597	HELU-S-RK-45-CU-UL 10-5	10,0	5,3	4,5	12,0	5,5	100	o. r.	o. r.	o. r.
907598	HELU-S-RK-45-CU-UL 10-6	10,0	6,4	4,5	12,0	5,8	100	o. r.	o. r.	o. r.
907599	HELU-S-RK-45-CU-UL 10-8	10,0	8,4	4,5	15,0	6,5	100	o. r.	o. r.	o. r.
907600	HELU-S-RK-45-CU-UL 10-10	10,0	10,5	4,5	18,0	6,6	100	o. r.	o. r.	o. r.
907601	HELU-S-RK-45-CU-UL 16-5	16,0	5,3	5,5	12,0	9,5	100	o. r.	o. r.	o. r.
907467	HELU-S-RK-45-CU-UL 16-6	16,0	6,4	5,5	12,0	10,2	100	o. r.	o. r.	o. r.
907468	HELU-S-RK-45-CU-UL 16-8	16,0	8,4	5,5	15,0	11,7	100	o. r.	o. r.	o. r.
907469	HELU-S-RK-45-CU-UL 16-10	16,0	10,5	5,5	18,0	11,7	100	o. r.	o. r.	o. r.
907470	HELU-S-RK-45-CU-UL 25-6	25,0	6,4	7,0	15,0	13,9	100	o. r.	o. r.	o. r.
907471	HELU-S-RK-45-CU-UL 25-8	25,0	8,4	7,0	16,0	15,1	100	o. r.	o. r.	o. r.
907472	HELU-S-RK-45-CU-UL 25-10	25,0	10,5	7,0	18,0	16,6	100	o. r.	o. r.	o. r.
907473	HELU-S-RK-45-CU-UL 25-12	25,0	13,0	7,0	20,0	17,0	100	o. r.	o. r.	o. r.
907474	HELU-S-RK-45-CU-UL 35-6	35,0	6,4	8,5	17,0	21,7	50	o. r.	o. r.	o. r.
907475	HELU-S-RK-45-CU-UL 35-8	35,0	8,4	8,5	17,0	22,3	50	o. r.	o. r.	o. r.
907476	HELU-S-RK-45-CU-UL 35-10	35,0	10,5	8,5	20,0	23,4	50	o. r.	o. r.	o. r.
907477	HELU-S-RK-45-CU-UL 35-12	35,0	13,0	8,5	22,0	24,0	50	o. r.	o. r.	o. r.
907478	HELU-S-RK-45-CU-UL 50-6	50,0	6,4	10,0	20,0	29,4	50	o. r.	o. r.	o. r.
907479	HELU-S-RK-45-CU-UL 50-8	50,0	8,4	10,0	20,0	33,4	50	o. r.	o. r.	o. r.
907480	HELU-S-RK-45-CU-UL 50-10	50,0	10,5	10,0	20,0	36,5	50	o. r.	o. r.	o. r.
907481	HELU-S-RK-45-CU-UL 50-12	50,0	13,0	10,0	23,0	36,5	50	o. r.	o. r.	o. r.
907482	HELU-S-RK-45-CU-UL 70-8	70,0	8,4	12,0	24,0	49,0	25	o. r.	o. r.	o. r.
907483	HELU-S-RK-45-CU-UL 70-10	70,0	10,5	12,0	24,0	52,3	25	o. r.	o. r.	o. r.
907484	HELU-S-RK-45-CU-UL 70-12	70,0	13,0	12,0	24,0	53,4	25	o. r.	o. r.	o. r.
907485	HELU-S-RK-45-CU-UL 95-8	95,0	8,4	13,5	26,0	61,8	25	o. r.	o. r.	o. r.
907486	HELU-S-RK-45-CU-UL 95-10	95,0	10,5	13,5	26,0	62,0	25	o. r.	o. r.	o. r.
907487	HELU-S-RK-45-CU-UL 95-12	95,0	13,0	13,5	26,0	62,0	25	o. r.	o. r.	o. r.
907488	HELU-S-RK-45-CU-UL 95-16	95,0	17,0	13,5	28,0	68,0	25	o. r.	o. r.	o. r.
907489	HELU-S-RK-45-CU-UL 120-8	120,0	8,4	15,0	29,0	78,0	25	o. r.	o. r.	o. r.
907490	HELU-S-RK-45-CU-UL 120-10	120,0	10,5	15,0	29,0	89,0	25	o. r.	o. r.	o. r.
907491	HELU-S-RK-45-CU-UL 120-12	120,0	13,0	15,0	29,0	89,1	25	o. r.	o. r.	o. r.
907492	HELU-S-RK-45-CU-UL 120-16	120,0	17,0	15,0	30,0	93,1	25	o. r.	o. r.	o. r.
907493	HELU-S-RK-45-CU-UL 150-8	150,0	8,4	16,8	31,0	113,1	25	o. r.	o. r.	o. r.
907494	HELU-S-RK-45-CU-UL 150-10	150,0	10,5	16,8	31,0	98,0	25	o. r.	o. r.	o. r.
907495	HELU-S-RK-45-CU-UL 150-12	150,0	13,0	16,8	31,0	96,8	25	o. r.	o. r.	o. r.
907496	HELU-S-RK-45-CU-UL 150-16	150,0	17,0	16,8	31,0	101,2	25	o. r.	o. r.	o. r.
907497	HELU-S-RK-45-CU-UL 150-20	150,0	21,0	16,8	35,0	101,2	25	o. r.	o. r.	o. r.
907498	HELU-S-RK-45-CU-UL 185-10	185,0	10,5	19,0	35,0	123,5	20	o. r.	o. r.	o. r.
907499	HELU-S-RK-45-CU-UL 185-12	185,0	13,0	19,0	35,0	122,4	20	o. r.	o. r.	o. r.

Continuation ►

HELU-S-RK-45-CU-UL Copper tubular cable lug - 45° angled



eye type

Part no. 45°	Type	Cross-section mm ²	a mm	d mm	b mm	Weight kg / 1000 items	Unit	Net EUR/ 100 items at a purchase of		
								up to 100	101 - 500	501 - 1000
907500	HELU-S-RK-45-CU-UL 185-16	185,0	17,0	19,0	35,0	128,4	20	o. r.	o. r.	o. r.
907501	HELU-S-RK-45-CU-UL 185-20	185,0	21,0	19,0	35,0	139,9	20	o. r.	o. r.	o. r.
907502	HELU-S-RK-45-CU-UL 240-12	240,0	13,0	21,0	38,0	154,6	15	o. r.	o. r.	o. r.
907503	HELU-S-RK-45-CU-UL 240-16	240,0	17,0	21,0	38,0	165,1	15	o. r.	o. r.	o. r.
907504	HELU-S-RK-45-CU-UL 240-20	240,0	21,0	21,0	38,0	170,4	15	o. r.	o. r.	o. r.
907505	HELU-S-RK-45-CU-UL 300-12	300,0	13,0	24,0	43,0	257,0	15	o. r.	o. r.	o. r.
907506	HELU-S-RK-45-CU-UL 300-16	300,0	17,0	24,0	43,0	256,8	15	o. r.	o. r.	o. r.
907507	HELU-S-RK-45-CU-UL 300-20	300,0	21,0	24,0	43,0	273,0	15	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request