

HELU-S-PK-CU Tubular compression cable lugs - straight

uninsulated



Tubular cable lugs HELU-S-PK-CU


Non-insulated tubular cable lugs in eye type design for conductor arrangement RM.
Tube dimensions to DIN 46235.

Material

Socket: Copper according to DIN EN 13600
Surface: tin plated or optionally uncoated

Note

Code type indicates the required hexagonal clamping insert.
Compression instruction and instruction for assembly see chapter "Technical information".



Diameter

- a Diameter of the boring
- d Inner diameter of the cable insertion
- b Flange width
- l Length till middle of the boring

eye type

Part no.	Type	Cross-section mm ²	a mm	d mm	b mm	l mm	Code type	Weight kg / 1000 items	Unit	Net EUR/100 items at a purchase of		
										up to 100	101 - 500	501 - 1000
907679	HELU-S-PK-CU 6-8	6,0	8,4	3,5	13,0	26,0	5	3,1	100	o. r.	o. r.	o. r.
907682	HELU-S-PK-CU 10-8	10,0	8,4	4,4	13,0	28,0	6	3,8	100	o. r.	o. r.	o. r.
907683	HELU-S-PK-CU 10-10	10,0	10,5	4,4	15,0	29,0	6	3,8	100	o. r.	o. r.	o. r.
907684	HELU-S-PK-CU 16-5	16,0	5,3	5,5	13,0	36,0	8	12,2	100	o. r.	o. r.	o. r.
907688	HELU-S-PK-CU 16-12	16,0	13,0	5,5	19,0	40,0	8	13,5	100	o. r.	o. r.	o. r.
907693	HELU-S-PK-CU 25-16	25,0	17,0	7,0	22,0	45,0	10	19,9	100	o. r.	o. r.	o. r.
907694	HELU-S-PK-CU 35-6	35,0	6,4	8,2	17,5	42,5	12	31,2	100	o. r.	o. r.	o. r.
907698	HELU-S-PK-CU 35-16	35,0	17,0	8,2	28,0	47,0	12	31,4	100	o. r.	o. r.	o. r.
907699	HELU-S-PK-CU 35-20	35,0	21,0	8,2	30,0	53,0	12	37,3	100	o. r.	o. r.	o. r.
907700	HELU-S-PK-CU 50-6	50,0	6,4	9,8	20,0	52,0	14	46,7	100	o. r.	o. r.	o. r.
907704	HELU-S-PK-CU 50-14	50,0	15,0	9,8	26,0	53,5	14	49,4	100	o. r.	o. r.	o. r.
907706	HELU-S-PK-CU 50-20	50,0	21,0	9,8	30,0	55,6	14	55,6	100	o. r.	o. r.	o. r.
907710	HELU-S-PK-CU 70-14	70,0	15,0	11,3	24,0	55,5	16	60,0	50	o. r.	o. r.	o. r.
907712	HELU-S-PK-CU 70-20	70,0	21,0	11,3	31,0	61,0	16	69,9	50	o. r.	o. r.	o. r.
907713	HELU-S-PK-CU 95-8	95,0	8,4	13,5	28,0	65,0	18	93,6	50	o. r.	o. r.	o. r.
907714	HELU-S-PK-CU 95-14	95,0	15,0	13,5	28,0	65,5	18	94,3	50	o. r.	o. r.	o. r.
907717	HELU-S-PK-CU 120-8	120,0	8,4	15,5	31,0	70,0	20	113,5	50	o. r.	o. r.	o. r.
907718	HELU-S-PK-CU 120-14	120,0	15,0	15,5	31,0	70,0	20	114,1	50	o. r.	o. r.	o. r.
907721	HELU-S-PK-CU 150-8	150,0	8,4	17,0	34,0	79,0	22	164,0	25	o. r.	o. r.	o. r.
907723	HELU-S-PK-CU 150-14	150,0	15,0	17,0	34,0	78,0	22	164,9	25	o. r.	o. r.	o. r.
907725	HELU-S-PK-CU 185-8	185,0	8,4	19,0	37,0	83,0	25	185,0	25	o. r.	o. r.	o. r.
907727	HELU-S-PK-CU 185-14	185,0	15,0	19,0	37,0	82,0	25	189,6	25	o. r.	o. r.	o. r.
907729	HELU-S-PK-CU 240-10	240,0	10,5	21,5	42,0	92,0	28	271,0	20	o. r.	o. r.	o. r.
907730	HELU-S-PK-CU 240-14	240,0	15,0	21,5	42,5	92,0	28	267,3	20	o. r.	o. r.	o. r.
907732	HELU-S-PK-CU 300-10	300,0	10,5	24,5	48,5	104,0	32	348,0	10	o. r.	o. r.	o. r.
907733	HELU-S-PK-CU 300-12	300,0	13,0	24,5	48,5	104,0	32	345,0	10	o. r.	o. r.	o. r.
907734	HELU-S-PK-CU 300-14	300,0	15,0	24,5	48,5	104,0	32	346,0	10	o. r.	o. r.	o. r.
907735	HELU-S-PK-CU 400-10	400,0	10,5	27,5	55,0	117,0	38	715,5	5	o. r.	o. r.	o. r.
907736	HELU-S-PK-CU 400-12	400,0	13,0	27,5	55,0	117,0	38	717,0	5	o. r.	o. r.	o. r.
907737	HELU-S-PK-CU 400-14	400,0	15,0	27,5	55,0	117,0	38	719,8	5	o. r.	o. r.	o. r.
907738	HELU-S-PK-CU 500-12	500,0	13,0	31,0	60,0	130,0	42	869,2	5	o. r.	o. r.	o. r.
907739	HELU-S-PK-CU 500-14	500,0	15,0	31,0	60,0	130,0	42	875,0	5	o. r.	o. r.	o. r.

Continuation ▶

HELU-S-PK-CU Tubular compression cable lugs - straight

uninsulated

eye type

Part no.	Type	Cross-section mm ²	a mm	d mm	b mm	l mm	Code type	Weight kg / 1000 items	Unit	Net EUR/100 items at a purchase of		
										up to 100	101 - 500	501 - 1000
907740	HELU-S-PK-CU 500-16	500,0	17,0	31,0	60,0	130,0	42	889,0	5	o. r.	o. r.	o. r.
907741	HELU-S-PK-CU 625-12	625,0	13,0	34,5	63,0	135,0	44	842,7	5	o. r.	o. r.	o. r.
907742	HELU-S-PK-CU 625-14	625,0	15,0	34,5	63,0	135,0	44	838,9	5	o. r.	o. r.	o. r.
907743	HELU-S-PK-CU 625-16	625,0	17,0	34,5	63,0	135,0	44	820,5	5	o. r.	o. r.	o. r.
907745	HELU-S-PK-CU 800-14	800,0	15,0	16,0	75,0	165,0	100	1486,0	2	o. r.	o. r.	o. r.
907746	HELU-S-PK-CU 800-16	800,0	17,0	40,0	75,0	165,0	100	1494,2	2	o. r.	o. r.	o. r.
907748	HELU-S-PK-CU 1000-16	1000,0	17,0	44,0	83,0	167,0	58	1937,0	2	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request