


KW plastic helix



KW plastic helix

Plastic helix made of polyethylene. Protects wiring harnesses, wires and lines. Bundles and binds single wires and provides mechanical protection for loosely installed or moving cables and lines.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material

Polyethylene

- halogen-free

Note

Other materials or colours on request.

Technical data

Temperature range: -30°C up to +80°C

Part no.	Size	Colour	Bundle Ø mm	Per metres	Net EUR/100 metres at a purchase of		
					up to 100	101 - 500	501 - 1000
91000	6	transparent	5,0 - 20,0	25	o. r.	o. r.	o. r.
91001	6	black	5,0 - 20,0	25	o. r.	o. r.	o. r.
96659	6	yellow	5,0 - 20,0	25	o. r.	o. r.	o. r.
96891	6	orange	5,0 - 20,0	25	o. r.	o. r.	o. r.
91002	12	transparent	12,0 - 40,0	25	o. r.	o. r.	o. r.
91003	12	black	12,0 - 40,0	25	o. r.	o. r.	o. r.
96658	12	yellow	10,0 - 40,0	25	o. r.	o. r.	o. r.
97042	12	orange	10,0 - 40,0	25	o. r.	o. r.	o. r.
96300	22	transparent	20,0 - 150,0	25	o. r.	o. r.	o. r.
96299	22	black	20,0 - 150,0	25	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request