

# Solderless terminals

insulated



## Insulated solderless terminals

Insulated solderless terminals for cross sections of 0.25 to 6.0 mm<sup>2</sup>.

Simple cable inlet through Easy-Entry (expanded sleeve).

Insulated with high dielectric strength.


## Material

Socket: Copper  
Surface: tinned

Insulation: Partially-insulated, PA

## Technical data

Temperature range: -60°C up to +125°C



### butt connector

Part no.	Type	Colour	Cross-section mm <sup>2</sup>	Connection bolts M	Design	Unit	Net EUR/100 items at a purchase of		
							up to 500	501 - 1000	1001 - 5000
91426	HAA 15	red	0,5 - 1,5	-	Connector	100	o. r.	o. r.	o. r.
91427	HBB 25	blue	1,5 - 2,5	-	Connector	100	o. r.	o. r.	o. r.
91429	HCC 6	yellow	2,5 - 6,0	-	Connector	100	o. r.	o. r.	o. r.

### closed end-splices

Part no.	Type	Colour	Cross-section mm <sup>2</sup>	Connection bolts M	Design	Unit	Net EUR/100 items at a purchase of		
							up to 500	501 - 1000	1001 - 5000
91398	HAJ	transparent	0,5 - 1,5	-	Terminal connector	100	o. r.	o. r.	o. r.
91428	HBJ	transparent	1,5 - 2,5	-	Terminal connector	100	o. r.	o. r.	o. r.
91430	H CJ	transparent	2,5 - 6,0	-	Terminal connector	100	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request