

DUO core end sleeves

insulated - for 2 conductors



DUO

Insulated DUO core end sleeves for insertion of 2 conductors prevent stripped wires from fanning.

The hopper-shaped plastic collar enables them to be pushed easily onto the wires.

To DIN, ZF, and Telemecanique colour code.

Material

Socket: copper
Surface: tinned

Insulating shroud: polypropylene


Note

Versions:
N = normal
L = long

Technical data

Temperature range: up to +105°C

Temperature range temporary up to +120°C



Dimensions

L Total length
l Stick length

Part no.	Size mm ²	Colour	Colour code	Total length mm	Stick length mm	Unit	Net EUR/100 items at a purchase of		
							up to 5000	5001 - 10000	10001 - 50000
91622	2x 0.5 / N	white	DIN	15,0	8,0	500	o. r.	o. r.	o. r.
91623	2x 0.5 / N	orange	Z+F	15,0	8,0	500	o. r.	o. r.	o. r.
91652	2x 0.75 / L	grey	DIN	17,0	10,0	500	o. r.	o. r.	o. r.
91671	2x 0.75 / L	light blue	Telemecanique	17,0	10,0	500	o. r.	o. r.	o. r.
91651	2x 0.75 / L	white	Z+F	17,0	10,0	500	o. r.	o. r.	o. r.
90125	2x 0.75 / N	grey	DIN	15,0	8,0	500	o. r.	o. r.	o. r.
91661	2x 0.75 / N	light blue	DIN	15,0	8,0	500	o. r.	o. r.	o. r.
91624	2x 0.75 / N	white	Z+F	15,0	8,0	500	o. r.	o. r.	o. r.
91653	2x 1 / L	red	DIN	17,0	10,0	500	o. r.	o. r.	o. r.
91654	2x 1 / L	yellow	Z+F	17,0	10,0	500	o. r.	o. r.	o. r.
90126	2x 1 / N	red	DIN	15,0	8,0	500	o. r.	o. r.	o. r.
91625	2x 1 / N	yellow	Z+F	15,0	8,0	500	o. r.	o. r.	o. r.
91655	2x 1.5 / L	black	DIN	20,0	12,0	500	o. r.	o. r.	o. r.
91672	2x 1.5 / L	red	Z+F	20,0	12,0	500	o. r.	o. r.	o. r.
90127	2x 1.5 / N	black	DIN	16,0	8,0	500	o. r.	o. r.	o. r.
91662	2x 1.5 / N	red	Z+F	16,0	8,0	500	o. r.	o. r.	o. r.
91656	2x 2.5 / L	blue	DIN	21,5	13,0	250	o. r.	o. r.	o. r.
91673	2x 2.5 / L	grey	Telemecanique	21,5	13,0	250	o. r.	o. r.	o. r.
90128	2x 2.5 / N	blue	DIN	18,5	10,0	250	o. r.	o. r.	o. r.
91663	2x 2.5 / N	grey	Telemecanique	18,5	10,0	250	o. r.	o. r.	o. r.
91626	2x 4 / N	grey	DIN	23,0	12,0	100	o. r.	o. r.	o. r.
91664	2x 4 / N	orange	Telemecanique	23,0	12,0	100	o. r.	o. r.	o. r.
91627	2x 6 / N	yellow	DIN	26,0	14,0	100	o. r.	o. r.	o. r.
91665	2x 6 / N	green	Telemecanique	26,0	14,0	100	o. r.	o. r.	o. r.
91666	2x 6 / N	black	Z+F	26,0	14,0	100	o. r.	o. r.	o. r.
91628	2x 10 / N	red	DIN	26,0	14,0	100	o. r.	o. r.	o. r.
91667	2x 10 / N	brown	Telemecanique	26,0	14,0	100	o. r.	o. r.	o. r.
91668	2x 10 / N	ivory	Z+F	26,0	14,0	100	o. r.	o. r.	o. r.
91629	2x 16 / N	blue	DIN	30,0	14,0	50	o. r.	o. r.	o. r.
91669	2x 16 / N	ivory	Telemecanique	30,0	14,0	50	o. r.	o. r.	o. r.
91670	2x 16 / N	green	Z+F	30,0	14,0	50	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request