

# ADI-B core end sleeves

insulated



## ADI-B

Tape products for processing with Stripax-Plus (strip products) or automatic crimpers (coil products).

Insulated core end sleeves prevent stripped wires from fanning.

The hopper-shaped plastic collar enables them to be pushed easily onto the wires.

## Material

Socket: copper  
Surface: tinned


Insulating shroud: polypropylene

## Note

Delivery formats:  
Strips: 1 item = 10 strips x 50 pcs.  
Coils: Endless on cardboard coil

## Technical data

Temperature range: up to +105°C  
Temperature range temporary up to +120°C



## Dimensions

L Total length  
I Stick length

## strip

Part no.	Size mm <sup>2</sup>	Colour	Colour code	Total length mm	Stick length mm	Unit	Net EUR/100 items at a purchase of		
							up to 5000	5001 - 10000	10001 - 50000
91912	0,5	white	DIN	14,0	8,0	500	o. r.	o. r.	o. r.
91913	0,5	orange	Z+F	14,0	8,0	500	o. r.	o. r.	o. r.
91914	0,75	grey	DIN	14,0	8,0	500	o. r.	o. r.	o. r.
91915	0,75	white	Z+F	14,0	8,0	500	o. r.	o. r.	o. r.
91916	0,75	light blue	Telemecanique	14,0	8,0	500	o. r.	o. r.	o. r.
91917	1,0	red	DIN	14,0	8,0	500	o. r.	o. r.	o. r.
91918	1,0	yellow	Z+F	14,0	8,0	500	o. r.	o. r.	o. r.
91919	1,5	black	DIN	14,0	8,0	500	o. r.	o. r.	o. r.
91920	1,5	red	Z+F	14,0	8,0	500	o. r.	o. r.	o. r.
91921	2,5	blue	DIN	14,0	8,0	500	o. r.	o. r.	o. r.
91922	2,5	grey	Telemecanique	14,0	8,0	500	o. r.	o. r.	o. r.

## coils

Part no.	Size mm <sup>2</sup>	Colour	Colour code	Total length mm	Stick length mm	Unit	Net EUR/100 items at a purchase of		
							up to 5000	5001 - 10000	10001 - 50000
93036	0,5	white	DIN	14,0	8,0	10000	o. r.	o. r.	o. r.
93037	0,5	orange	Z+F	14,0	8,0	10000	o. r.	o. r.	o. r.
93038	0,75	light blue	Telemecanique	14,0	8,0	10000	o. r.	o. r.	o. r.
93039	0,75	white	Z+F	14,0	8,0	10000	o. r.	o. r.	o. r.
93040	0,75	grey	DIN	14,0	8,0	10000	o. r.	o. r.	o. r.
93041	1,0	red	DIN	14,0	8,0	7500	o. r.	o. r.	o. r.
93042	1,0	yellow	Z+F	14,0	8,0	7500	o. r.	o. r.	o. r.
93043	1,5	black	DIN	14,0	8,0	7500	o. r.	o. r.	o. r.
93046	1,5	red	Z+F	14,0	8,0	7500	o. r.	o. r.	o. r.
93047	2,5	grey	Telemecanique	14,0	8,0	5000	o. r.	o. r.	o. r.
93048	2,5	blue	DIN	14,0	8,0	5000	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request