

FLEV-S outdoor termination, shrinking type



FLEV-S

Outside end seals for all single-conductor and three-conductor medium-range voltage plastic cables with differing conductor layers and sheath designs up to 18/30(36)kV.

Properties

- Safe field effect
- Simple assembly
- Wider application range
- Excellent external layer behaviour
- Unlimited conductivity
- Immediately operational

Scope of delivery

- Packing unit: 1
- suspensible silicon control element
- sealing band
- creeping current resistant, weather-proof heat shrink-on tube
- assembly instruction
- suspensible silicone sheds

Note

- An additional earthing kit is required for cables with copper sheath.
- Without terminals.
- 1 unit = 1 set with 3 items.

single core

Part no.	Type	Nominal voltage Uo/U(Um)	Cross-section mm ²	Unit	Net EUR/item at a purchase of		
					1	2 - 5	6 - 10
93360	FLEV-S12/1	6/10kV	10,0 - 25,0	1	o. r.	o. r.	o. r.
93361	FLEV-S12/1	6/10kV	25,0 - 95,0	1	o. r.	o. r.	o. r.
94426	FLEV-S12/1	6/10kV	95,0 - 240,0	1	o. r.	o. r.	o. r.
93362	FLEV-S12/1	6/10kV	150,0 - 400,0	1	o. r.	o. r.	o. r.
93363	FLEV-S12/1	6/10kV	240,0 - 500,0	1	o. r.	o. r.	o. r.
94427	FLEV-S12/1	6/10kV	400,0 - 800,0	1	o. r.	o. r.	o. r.
94428	FLEV-S12/1	6/10kV	800,0 - 1000,0	1	o. r.	o. r.	o. r.
94429	FLEV-S24/1	12/20kV	10,0 - 35,0	1	o. r.	o. r.	o. r.
93364	FLEV-S24/1	12/20kV	25,0 - 150,0	1	o. r.	o. r.	o. r.
93365	FLEV-S24/1	12/20kV	70,0 - 240,0	1	o. r.	o. r.	o. r.
93366	FLEV-S24/1	12/20kV	120,0 - 300,0	1	o. r.	o. r.	o. r.
93380	FLEV-S24/1	12/20kV	240,0 - 500,0	1	o. r.	o. r.	o. r.
94430	FLEV-S24/1	12/20kV	630,0 - 1000,0	1	o. r.	o. r.	o. r.
93367	FLEV-S36/1	18/30kV	35,0 - 70,0	1	o. r.	o. r.	o. r.
93368	FLEV-S36/1	18/30kV	50,0 - 150,0	1	o. r.	o. r.	o. r.
93369	FLEV-S36/1	18/30kV	150,0 - 400,0	1	o. r.	o. r.	o. r.
93370	FLEV-S36/1	18/30kV	500,0 - 800,0	1	o. r.	o. r.	o. r.

3-core

Part no.	Type	Nominal voltage Uo/U(Um)	Cross-section mm ²	Unit	Net EUR/item at a purchase of		
					1	2 - 5	6 - 10
94443	FLEV-S12/3	6/10kV	10,0 - 25,0	1	o. r.	o. r.	o. r.
93371	FLEV-S12/3	6/10kV	25,0 - 95,0	1	o. r.	o. r.	o. r.
93372	FLEV-S12/3	6/10kV	95,0 - 240,0	1	o. r.	o. r.	o. r.
93373	FLEV-S12/3	6/10kV	150,0 - 400,0	1	o. r.	o. r.	o. r.
94444	FLEV-S24/3	12/20kV	10,0 - 35,0	1	o. r.	o. r.	o. r.
94445	FLEV-S24/3	12/20kV	25,0 - 95,0	1	o. r.	o. r.	o. r.
94446	FLEV-S24/3	12/20kV	70,0 - 240,0	1	o. r.	o. r.	o. r.
94447	FLEV-S24/3	12/20kV	120,0 - 300,0	1	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request