

MSVM-A medium voltage straight-through joint with slip-on method

single core



MSVM-A

Medium voltage straight-through joint with slip-on method for connecting single-core plastic power cables up to 12/20(24)kV. For connecting cables with differing cross-sections, conductor materials and cable designs with regard to external conductor layer and shielding.

Properties

- Quick and simple assembly
- Large cross-sections
- Unlimited conductivity
- Immediately operational

Scope of delivery

- Packing unit: 1
- two suspensible silicon control elements
- one-piece silicon insulating body with integrated conductor smoothing
- thick-walled heat shrink-on tube
- copper fabric shielding
- assembly instruction

single core

Part no.	Type	Nominal voltage U ₀ /U(U _m)	Cross-section mm ²	Unit	Net EUR/item at a purchase of		
					1	2 - 5	6 - 10
94350	MSVM-A12	6/10kV	25,0 - 95,0	1	o. r.	o. r.	o. r.
94351	MSVM-A12	6/10kV	95,0 - 240,0	1	o. r.	o. r.	o. r.
94352	MSVM-A12	6/10kV	50,0 - 240,0	1	o. r.	o. r.	o. r.
94353	MSVM-A12	6/10kV	150,0 - 400,0	1	o. r.	o. r.	o. r.
94355	MSVM-A24	12/20kV	16,0 - 120,0	1	o. r.	o. r.	o. r.
94356	MSVM-A24	12/20kV	35,0 - 95,0	1	o. r.	o. r.	o. r.
94357	MSVM-A24	12/20kV	70,0 - 240,0	1	o. r.	o. r.	o. r.
94358	MSVM-A24	12/20kV	70,0 - 240,0	1	o. r.	o. r.	o. r.
94359	MSVM-A24	12/20kV	35,0 - 240,0	1	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request