

Solderless terminals

insulated



Insulated squeeze snap-on connection

Insulated squeeze snap-on connection for cross sections of 0.5 to 6.0 mm².
Simple cable inlet through Easy-Entry (expanded sleeve).
Insulated with high dielectric strength.

Material

Socket: copper
Surface: tinned

Insulation: fully-insulated

Note

Versions:
Flat connector (insulated / fully insulated)
Flat connector sleeves (insulated / fully insulated)
Flat connector distributor

Technical data

Temperature range: -25°C up to +105°C

blade receptacle, all-insulated

Part no.	Type	Colour	Cross-section mm ²	Flat plug size mm	Design	Unit	Net EUR/100 items at a purchase of		
							up to 500	501 - 1000	1001 - 5000
96574	RA 28 V0	red	0,5 - 1,0	flat, 2.8 x 0.8 mm	Sleeve	100	o. r.	o. r.	o. r.
96328	RA 29 V0	red	0,5 - 1,5	flat, 2.8 x 0.5 mm	Sleeve	100	o. r.	o. r.	o. r.
96329	RA 48 V0	red	0,5 - 1,5	flat, 4.8 x 0.8 mm	Sleeve	100	o. r.	o. r.	o. r.
96330	RA 49 V0	red	0,5 - 1,5	flat, 4.8 x 0.5 mm	Sleeve	100	o. r.	o. r.	o. r.
96334	RA 63 V0	red	0,5 - 1,5	flat, 6.3 x 0.8 mm	Sleeve	100	o. r.	o. r.	o. r.
96331	RB 48 V0	blue	1,5 - 2,5	flat, 4.8 x 0.8 mm	Sleeve	100	o. r.	o. r.	o. r.
96332	RB 49 V0	blue	1,5 - 2,5	flat, 4.8 x 0.5 mm	Sleeve	100	o. r.	o. r.	o. r.
96335	RB 63 V0	blue	1,5 - 2,5	flat, 6.3 x 0.8 mm	Sleeve	100	o. r.	o. r.	o. r.
96333	RC 63 V0	yellow	2,5 - 6,0	flat, 6.3 x 0.8 mm	Sleeve	100	o. r.	o. r.	o. r.

flat distributor

Part no.	Type	Colour	Cross-section mm ²	Flat plug size mm	Design	Unit	Net EUR/100 items at a purchase of		
							up to 500	501 - 1000	1001 - 5000
91436	RA 63 T	red	0,5 - 1,5	flat, 6.3 x 0.8 mm	Distributor	100	o. r.	o. r.	o. r.
91441	RB 63 T	blue	1,5 - 2,5	flat, 6.3 x 0.8 mm	Distributor	100	o. r.	o. r.	o. r.
94929	RC 63 T	yellow	2,5 - 6,0	flat, 6.3 x 0.8 mm	Distributor	100	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request